



CombiSteel

DEMININATION:

Static refrigerated well with 160 mm depth width 610 mm 5 GN 1/1 capacity DDCSB6-160-5 230V 1N 50/60 Hz climate class IV cold group Included refrigerant gas R290.

DESCRIPTION:

- Static refrigerated well specially designed to hold, display and serve chilled food (e.g. fruits, desserts, yogurts, cold appetizers, presented on plates/ramekins, etc.) and beverages (bottles, cans) keeping displayed product at optimum temperatures during service time.
- Manufactured in stainless steel with satin finish.
- Static refrigerated well with depth to exhibit pans of different heights
- Well with rounded corners inside to make cleaning operations easier, ensuring maximum hygiene.
- Static well refrigeration system by expanded copper coil located in its base.
- Polyurethane insulation with ecological injection, CFC-free, with high-density (40 kg/m³) allowing energy savings by reducing loss of cold air.
- Control panel with digital thermostat, protected by the structure perimeter, avoiding hindrances in their daily use.
- Control panel with 1-meter long cable, allowing to be installed on another element, e.g. furniture under the drop-in element.
- Electronic thermostat, with digital display, to control and regulate the temperature on the static well at the desired set point.
- Stamped drain on the well, to discharge condensation water. A connection from the drain to the sanitation network is recommended.
- Automatic evaporation system of defrost water as an accessory.
- Robust structure with 13 mm thick overlap, once element is dropped-in on the worktop, ensuring cleanness and aesthetics.
- Prepared for installation of a light foodshield, easily mounted on the structure by means of threaded plates.
- Prepared for installation of a digital thermometer facing the public.
- Digital thermostat allows turning on, at the same time, refrigerated element and foodshield with light.
- Copper coil also on the sides of the well to improve performance.

POSSIBLE ACCESSORIES:

- FOODSHIELD WITH LIGHT
- NEUTRAL FOODSHIELD
- EVAPORATION KIT DEFROST WATER
- OVERFLOW PAN DEFROST WATER
- TOOL TO LIFT DROP-IN

DIMENSIONS:

X Width	1765 mm	X Gross width	1865 mm
Y Depth	610 mm	Y Gross depth	730 mm
Z Height	632 mm	Z Gross height	832 mm
Net Weight	70,0 kg	Gross Weight	80,0 kg
Net volume	0,680 m ³	Gross volume	1,145 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,305 kW
Voltage	220-240V
Phases	1N
Electric frequency	50/60Hz
Amperage (A)	1,36A

COLD TECHNICAL SPECIFICATIONS

Temperature	(+0°/ +8°)
Climate class	4
Refrigeration power	0,385 kW
Gas type	R-290
Cooling gas load	0,119 kg

CONNECTIONS TECHNICAL SPECIFICATIONS

Drain 1 diameter	1/2"
------------------	------




RACK TYPE DISHWASHERS. MARKETING

Cut-out Length (mm)	1740
Cut-out Width (mm)	585
Capacity (GN)	5 x GN1/1
Well type	Static refrigerated
Depth well (mm)	160
Bottle Ø 65 mm cap. In well	246
Ramekin Ø 130 mm cap. In well	61
Plate Ø 150mm capac. In well	46

7495.0065



CombiSteel



W = 610 mm	W = 720 mm
LE : 241 mm	LE : 241 mm
LD : 143 mm	LD : 143 mm
AE : 335 mm	AE : 390 mm
AD : 114 mm	AD : 169 mm

H ⊕ : - 538 mm

H ● : - 288 mm

				W = 610 mm	W = 720 mm
	X	Y	Z	V	V
2GN	790	698	304	573	683
3GN	1115	1023	629	573	683
4GN	1440	1348	954	573	683
5GN	1765	1673	1279	573	683
6GN	2090	1998	1604	573	683

7495.0065